



3 Pin Plug Socket Outlets

- 6A socket outlets are used in conjunction with 6A plugs to provide a pluggable connection to luminaires.
 - Complies with BS 6972 and BS 5733
- Suitable for use with standard Klik 3 pin plug
- S27 socket is supplied in plug-in ceiling rose, Cat. Ref. PCR2000
- S27 socket will accept A1 cover
- S26/TC socket is an S26 architrave socket pre-assembled with a trunking clamp

Description	Cat ref.
3 Pin Round Socket White	\$27

4 Pin with Auxiliary Plug Socket Outlets

klik.AX 6A socket outlets are used in conjunction with klik.AX 6A plugs to provide a pluggable connection to luminaires.
- Complies with BS 6972 and BS 5733

- Suitable for use with standard klik.LDS 3 pin plug
- Subable for use with standard kink.EDS 5 pin pidg
 S27 socket is supplied in plug-in ceiling rose, Cat. Ref. PCR2000
- S27 socket will accept A1 cover
- S26/TC socket is an S26 architrave socket pre-assembled with a trunking clamp
- All sockets have 5 terminations: line, neutral, CPC, auxiliary and loop-in
- Can be used with klik 3 or 4 pin plug

Description	Cat ref.
KLIK-AX 4-PIN ROUND SOCKET WHT	S64AX
4 PIN SOCKET BLACK 6A	S64BLACK



S64AX