



WXPPS12

IP66 Wall Switches

- Switches are from the unique and popular Sollysta White Moulded range.
- IP66 rating conforms to BS EN 60629:1992.
- Functional products tested and certified to appropriate British Standards.
- Robust and rugged enclosures to withstand the elements.
- Cable entries:
90 x 90 = 4x20, 1x20 & 1x25

| Description | Cat ref. |
|--|-----------------|
| IP66 10AX 1 Gang 2 Way Switch | WXPPS12 |
| IP66 10AX 2 Gang 2 Way Switch | WXPPS22 |
| IP66 20A 1 Gang 1 Way Double Pole Switch | WXDP84 |
| IP66 10A 1 Gang Press Bell Switch | WXPPS12B |



WXPS81

IP66 Socket Outlets

- Sockets are from the unique and popular Sollysta White Moulded range.
- IP66 rating conforms to BS EN 60629:1992.
- Functional products tested and certified to appropriate British Standards.
- Robust and rugged enclosures to withstand the elements.
- Unique double hinge allows lid to fully open through 180 degrees.
- Fixing point for padlock
- Cable entries:
103 x 116.5 = 4x20, 1x20 & 1x25
164 x 116.5 = 6x20, 1x20 & 1x25

| Description | Cat ref. |
|---|---------------|
| IP66 Single 13A Un-switched Socket | WXPS81 |
| IP66 Single 13A Double Pole Switched Socket | WXPS81 |
| IP66 Twin 13A Un-switched Socket | WXPS82 |
| IP66 Twin 13A Double Pole Switched Socket | WXPS82 |



WXPSSU83FO

IP66 Fused Connection Units

- Fused connection units are from the unique and popular Sollysta White Moulded range.
- IP66 rating conforms to BS EN 60629:1992.
- Functional products tested and certified to appropriate British Standards.
- Robust and rugged enclosures to withstand the elements.
- Unique double hinge allows lid to fully open through 180 degrees.
- Fixing point for padlock
- Cable entries:
103 x 116.5 = 4x20, 1x20 & 1x25

| Description | Cat ref. |
|--|-------------------|
| IP66 13A Double Pole Switched Fused Connection Unit with Flex Outlet | WXPSSU83FO |