

- Complies with BS EN 60669-2-4
- Rated conditional short circuit current (Inc) 1500A tested with Hager MTN150 6kA B curve MCB
- LED indication
- All terminal screws upward facing for ease of installation
- Clearly printed terminal marking
- Capacity of each terminal 2 x 6mm<sup>2</sup>, 1 x 10mm<sup>2</sup>
- WR references supplied with M3.5 x 30mm long fixing screws
- WF references supplied with M3.5 x 20mm long fixing screws



WRDP50NPSW

## Raised Plate 50A Double Pole Switch 1 Gang with LED Indicator

Description	Cat ref.
50A Double Pole Switch 1 Gang with LED Indicator Polished Steel White Insert	<b>WRDP50NPSW</b>
50A Double Pole Switch 1 Gang with LED Indicator Brushed Steel White	<b>WRDP50NBSW</b>
	<b>WRDP50NPSB</b>
50A Double Pole Switch 1 Gang with LED Indicator Brushed Steel Black	<b>WRDP50NBSB</b>



WFDP50NPSW

## Flat Plate 50A Double Pole Switch 1 Gang with LED Indicator

Description	Cat ref.
	<b>WFDP50NPSW</b>
50A Double Pole Switch 1 Gang with LED Indicator Brushed Steel White Insert	<b>WFDP50NBSW</b>
	<b>WFDP50NPSB</b>
50A Double Pole Switch 1 Gang with LED Indicator Brushed Steel Black Insert	<b>WFDP50NBSB</b>

## Flat Plate 50A Double Pole Switch 2 Gang with LED Indicator

Description	Cat ref.
50A Double Pole Switch 2 Gang with LED Indicator Brushed Steel Black Insert	<b>WFDP50VNBSB</b>
50A Double Pole Switch 2 Gang with LED Indicator Brushed Steel White Insert	<b>WFDP50VNBSW</b>

## Raised Plate 50A Double Pole Switch 2 Gang with LED Indicator

Description	Cat ref.
50A Double Pole Switch 2 Gang with LED Indicator Brushed Steel Black Insert	<b>WRDP50VNBSB</b>
50A Double Pole Switch 2 Gang with LED Indicator Brushed Steel White Insert	<b>WRDP50VNBSW</b>