

- Complies with BS 4177
- Switch and socket are double pole
- Twin earth as standard
- Main switch is suitable for isolation
- All terminals are upward facing for ease of installation
- Clearly printed terminal marking
- Capacity of terminals: 2 x 6.0mm<sup>2</sup>, 1 x 16.0mm<sup>2</sup>
- WR references supplied with M3.5 x 30mm long fixing screws
- WF references supplied with M3.5 x 20mm long fixing screws



## Raised Plate 45A Cooker Control Unit

Description	Cat ref.
45A Cooker Control Unit Polished Steel White Insert	<b>WRCC50NPSW</b>
45A Cooker Control Unit Brushed Steel White Insert	<b>WRCC50NBSW</b>
	<b>WRCC50NPSB</b>
45A Cooker Control Unit Brushed Steel Black Insert	<b>WRCC50NBSB</b>

WRCC50NPSW



## Flat Plate 45A Cooker Control Unit

Description	Cat ref.
	<b>WFCC50NPSW</b>
45A Cooker Control Unit Brushed Steel White Insert	<b>WFCC50NBSW</b>
	<b>WFCC50NPSB</b>
45A Cooker Control Unit Brushed Steel Black Insert	<b>WFCC50NBSB</b>

WFCC50NPSW