

## 3 Pin Pre-Wired LS0H 6A Plugs

6A pre-wired plugs are used to connect luminaires to a klik ceiling rose or marshalling box.

- Complies with BS 6972 and BS 5733
- Low smoke zero halogen flexible cord, complies with BS EN 50525-3-11
- All leads have prepared ends

Description	Cat ref.
P22 c/w 3 Core 0.75mm 2m LS0H DCA	<b>K4P222M075DCA</b>
P22 c/w 3 Core 0.75mm 3m LS0H DCA	<b>K4P223M075DCA</b>
P22 c/w 3 Core 0.75mm 4m LS0H DCA	<b>K4P224M075DCA</b>

## 4 Pin with Auxiliary Pre-Wired LS0H 6A Plugs - White

klik.AX 6A pre-wired plugs are used to connect luminaires to a klik ceiling rose or marshalling box.

- Complies with BS 6972 and BS 5733
- Low smoke zero halogen flexible cord, complies with BS EN 50525-3-11
- All leads have prepared ends

Description	Cat ref.
P64AX c/w 4 Core 0.75mm 2m LS0H DCA	<b>K4P64AX2M075DCA</b>
P64AX c/w 4 Core 0.75mm 3m LS0H DCA	<b>K4P64AX3M075DCA</b>
P64AX c/w 4 Core 0.75mm 4m LS0H DCA	<b>K4P64AX4M075DCA</b>
P64AX c/w 4 Core 1.00mm 2m LS0H DCA	<b>K4P64AX2M1DCA</b>
P64AX c/w 4 Core 1.00mm 3m LS0H DCA	<b>K4P64AX3M1DCA</b>
P64AX c/w 4 Core 1.00mm 4m LS0H DCA	<b>K4P64AX4M1DCA</b>
P64AX c/w 4 Core 1.00mm 5m LS0H DCA	<b>K4P64AX5M1DCA</b>

## 4 Pin with Auxiliary Pre-Wired LS0H 6A Plugs - Red

klik.AX 6A pre-wired plugs are used to connect luminaires to a klik ceiling rose or marshalling box.

- Complies with BS 6972 and BS 5733
- Low smoke zero halogen flexible cord, complies with BS EN 50525-3-11
- All leads have prepared ends

Description	Cat ref.
P64AXR c/w 4 Core 0.75mm 2m LS0H DCA	<b>K4P64AXR2M075DCA</b>
P64AXR c/w 4 Core 0.75mm 3m LS0H DCA	<b>K4P64AXR3M075DCA</b>
P64AXR c/w 4 Core 0.75mm 4m LS0H DCA	<b>K4P64AXR4M075DCA</b>
P64AXR c/w 4 Core 1.00mm 2m LS0H DCA	<b>K4P64AXR2M1DCA</b>
P64AXR c/w 4 Core 1.00mm 3m LS0H DCA	<b>K4P64AXR3M1DCA</b>
P64AXR c/w 4 Core 1.00mm 4m LS0H DCA	<b>K4P64AXR4M1DCA</b>
P64AXR c/w 4 Core 1.00mm 5m LS0H DCA	<b>K4P64AXR5M1DCA</b>