

IP66

Manufactured from a tough and durable thermoplastic, the Sollysta IP66 range is ideal for indoor and outdoor applications where wiring accessories may be vulnerable to the potentially harmful effects of dust or water ingress.

Our IP66 range features secure and easy to remove knockouts for cable entries, a unique dual action hinge and a 5mm padlock to prevent unauthorized use. You will also benefit from the features of our white moulded variant with as a unique neutral loop terminal and a patented safety shutter.

The IP66 rating assures total protection from ingress of dust and protection against powerful water jets.



WXPPS12

IP66 Wall Switches

- Switches are from the unique and popular Sollysta White Moulded range.
- IP66 rating conforms to BS EN 60629:1992.
- Functional products tested and certified to appropriate British Standards.
- Robust and rugged enclosures to withstand the elements.
- Cable entries:
90 x 90 = 4x20, 1x20 & 1x25

Description	Cat ref.
IP66 10AX 1 Gang 2 Way Switch	WXPPS12
IP66 10AX 2 Gang 2 Way Switch	WXPPS22
IP66 20A 1 Gang 1 Way Double Pole Switch	WXPD84
IP66 10A 1 Gang Press Bell Switch	WXPPS12B



WXPS81

IP66 Socket Outlets

- Sockets are from the unique and popular Sollysta White Moulded range.
- IP66 rating conforms to BS EN 60629:1992.
- Functional products tested and certified to appropriate British Standards.
- Robust and rugged enclosures to withstand the elements.
- Unique double hinge allows lid to fully open through 180 degrees.
- Fixing point for padlock
- Cable entries:
103 x 116.5 = 4x20, 1x20 & 1x25
164 x 116.5 = 6x20, 1x20 & 1x25

Description	Cat ref.
IP66 Single 13A Un-switched Socket	WXPS81
IP66 Single 13A Double Pole Switched Socket	WXPS81
IP66 Twin 13A Un-switched Socket	WXPS82
IP66 Twin 13A Double Pole Switched Socket	WXPS82



WXPSSU83FO

IP66 Fused Connection Units

- Fused connection units are from the unique and popular Sollysta White Moulded range.
- IP66 rating conforms to BS EN 60629:1992.
- Functional products tested and certified to appropriate British Standards.
- Robust and rugged enclosures to withstand the elements.
- Unique double hinge allows lid to fully open through 180 degrees.
- Fixing point for padlock
- Cable entries:
103 x 116.5 = 4x20, 1x20 & 1x25

Description	Cat ref.
IP66 13A Double Pole Switched Fused Connection Unit with Flex Outlet	WXPSSU83FO