

Klik 4 Pin

Today the pressure is on all areas of construction is to reduce costs. The installation speed of klik.LDS makes a significant contribution to both the on-site wiring and on-going maintenance costs, whether from a single outlet PCR or the muti-outlet marshalling box.

Klik 4 Pin - Marshalling Boxes	2
Klik 4 Pin - Plug-in Ceiling Roses and Covers	3
Klik 4 Pin - 3 and 4 Pin Pre-wired Plug-in Ceiling Roses	4
Klik 4 Pin - 3 and 4 Pin Plugs	5
Klik 4 Pin - Pre-wired Plugs	6
Klik 4 Pin - Plug Socket Outlets	7
Klik 4 Pin - Moulded Mounting Boxes	8



KLDS4

Marshalling Boxes

- Complies with BS 5733
- Main terminal rating 16 Amps
- Socket outlet rating 6 Amps
- Separate terminals for flexible conductors, rating 10 Amps
- Socket outlets accept either klik lighting (3 pin) plugs, klik.AX (4 pin) plugs and klik pre-wired leads

Description	Cat ref.
4 Way klik Lighting Distribution Unit	KLDS4
6 Way klik Lighting Distribution Unit	KLDS6
KLDS 6 WAY BLACK	KLDS6BLACK
8 Way klik Lighting Distribution Unit	KLDS8
10 Way klik Lighting Distribution Unit	KLDS10
12 Way klik Lighting Distribution Unit	KLDS12



PCR2000

3 Pin Plug-in Ceiling Rose & Cover

The 6A plug-in ceiling rose is used to offer a pluggable connection for luminaires. The luminaire can be connected and disconnected under load.

- Complies with BS 6972 and BS 5733:2010
- Sockets have 4 terminations: line, neutral, earth and loop-in
- Plugs have 3 terminations: line, neutral and CPC
- Fixing: 50.8mm Standard Diagonal (BESA)

Description	Cat ref.
Pre-Wired Plug-in Ceiling Rose White.	PCR2000
Plug-in Ceiling Rose Black	PCR2000BLACK



CR64AX

4 Pin with Auxiliary Plug-In Ceiling Rose & Cover

4 pin plus auxiliary 6A pre-wired plug-in ceiling roses are used to connect luminaires to a fixed wiring installations. Auxiliary contact available, a typical use is for emergency lighting.

- Complies with BS 6972 and BS 5733:2010
- Sockets have 5 terminations: line, neutral, CPC, auxiliary and loop-in
- Plugs have 4 terminations: line, neutral, CPC and auxiliary

Description	Cat ref.
4 Pin Plug in Ceiling Rose White	CR64AX
4 Pin Plug in Ceiling Rose Red	CR64AX/R



A1

Spare Ceiling Rose Covers

Description	Cat ref.
Ceiling Rose Cover White	A1
A1 COVER BLACK	A1BLACK
Ceiling Rose Cover Red	A1/R



PCR2000/LSF/2.0

3 Pin Pre-Wired LS0H 6A Plug-in Ceiling Rose

6A pre-wired plug-in ceiling roses are used to connect luminaires to a fixed wiring installation.

- Complies with BS 6972 and BS 5733
- Low smoke zero halogen flexible cord, complies with BS EN 50525-3-11
- All leads have prepared ends

Description	Cat ref.
PCR2000 c/w 3 Core 0.75mm 1m LS0H DCA	K4PCR20001M075DCA
PCR2000 c/w 3 Core 0.75mm 2m LS0H DCA	K4PCR20002M075DCA
PCR2000 c/w 3 Core 0.75mm 3m LS0H DCA	K4PCR20003M075DCA
PCR2000 c/w 3 Core 0.75mm 4m LS0H DCA	K4PCR20004M075DCA



CR64AX/LSF/4.0

4 Pin with Auxiliary Pre-Wired LS0H 6A Plug-in Ceiling Rose

klik.AX 6A pre-wired plug-in ceiling roses are used to connect luminaires to a fixed wiring installation.

- Complies with BS 6972 and BS 5733
- Low smoke zero halogen flexible cord, complies with BS EN 50525-3-11
- All leads have prepared ends

Description	Cat ref.
CR64AX c/w 4 Core 0.75mm2 4m LS0H Lead	CR64AX/LSF/4.0
CR64AX c/w 4 Core 0.75mm 1m LS0H DCA	K4PCR64AX1M075DCA
CR64AX c/w 4 Core 0.75mm2 2m LS0H Lead DCA	K4PCR64AX2M075DCA
CR64AX c/w 4 Core 0.75mm 3m LS0H DCA	K4PCR64AX3M075DCA
CR64AX c/w 4 Core 0.75mm 4m LS0H DCA	K4PCR64AX4M075DCA
CR64AX c/w 4 Core 1mm 2m LS0H DCA	K4PCR64AX2M1DCA
CR64AX c/w 4 Core 1mm 3m LS0H DCA	K4PCR64AX3M1DCA
CR64AX c/w 4 Core 1mm 4m LS0H DCA	K4PCR64AX4M1DCA
CR64AX c/w 4 Core 1mm 5m LS0H DCA	K4PCR64AX5M1DCA



3 Pin Plug

Klik 3 pin plugs are used to connect into a Klik 3 pin socket giving a pluggable connection to luminaires.
Complies with BS 6972 and BS 5733
Suitable for use with any klik 3 or 4 pin socket
P22 plug is supplied in a plug-in ceiling rose, cat ref. PCR2000
Plugs have 3 terminations: line, neutral and CPC

Warning

Plugs must not be fitted on the supply side of any installation - they must be connected to the load / fitting / appliance side of the installation.

P22

Description	Cat ref.
3 Pin Plug White	P22
3 PIN PLUG BLACK 6A	P22BLACK



4 Pin with Auxiliary Plug

klik 4 pin plugs are used to connect into the klik 4 pin sockets giving a pluggable connection to luminaires.

- Complies with BS 6972 and BS 5733
- Suitable for use with any klik.LDS 4 pin sockets
- Plugs have 4 terminations: line, neutral, CPC and auxiliary

Warning

Plugs must not be fitted on the supply side of any installation - they must be connected to the load / fitting / appliance side of the installation.

P64AX

Description	Cat ref.
4 Pin Plug White	P64AX
4 Pin Plug Red	P64AX/R

3 Pin Pre-Wired LS0H 6A Plugs

6A pre-wired plugs are used to connect luminaires to a klik ceiling rose or marshalling box.

- Complies with BS 6972 and BS 5733
- Low smoke zero halogen flexible cord, complies with BS EN 50525-3-11
- All leads have prepared ends

Description	Cat ref.
P22 c/w 3 Core 0.75mm 2m LS0H DCA	K4P222M075DCA
P22 c/w 3 Core 0.75mm 3m LS0H DCA	K4P223M075DCA
P22 c/w 3 Core 0.75mm 4m LS0H DCA	K4P224M075DCA

4 Pin with Auxiliary Pre-Wired LS0H 6A Plugs - White

klik.AX 6A pre-wired plugs are used to connect luminaires to a klik ceiling rose or marshalling box.

- Complies with BS 6972 and BS 5733
- Low smoke zero halogen flexible cord, complies with BS EN 50525-3-11
- All leads have prepared ends

Description	Cat ref.
P64AX c/w 4 Core 0.75mm 2m LS0H DCA	K4P64AX2M075DCA
P64AX c/w 4 Core 0.75mm 3m LS0H DCA	K4P64AX3M075DCA
P64AX c/w 4 Core 0.75mm 4m LS0H DCA	K4P64AX4M075DCA
P64AX c/w 4 Core 1.00mm 2m LS0H DCA	K4P64AX2M1DCA
P64AX c/w 4 Core 1.00mm 3m LS0H DCA	K4P64AX3M1DCA
P64AX c/w 4 Core 1.00mm 4m LS0H DCA	K4P64AX4M1DCA
P64AX c/w 4 Core 1.00mm 5m LS0H DCA	K4P64AX5M1DCA

4 Pin with Auxiliary Pre-Wired LS0H 6A Plugs - Red

klik.AX 6A pre-wired plugs are used to connect luminaires to a klik ceiling rose or marshalling box.

- Complies with BS 6972 and BS 5733
- Low smoke zero halogen flexible cord, complies with BS EN 50525-3-11
- All leads have prepared ends

Description	Cat ref.
P64AXR c/w 4 Core 0.75mm 2m LS0H DCA	K4P64AXR2M075DCA
P64AXR c/w 4 Core 0.75mm 3m LS0H DCA	K4P64AXR3M075DCA
P64AXR c/w 4 Core 0.75mm 4m LS0H DCA	K4P64AXR4M075DCA
P64AXR c/w 4 Core 1.00mm 2m LS0H DCA	K4P64AXR2M1DCA
P64AXR c/w 4 Core 1.00mm 3m LS0H DCA	K4P64AXR3M1DCA
P64AXR c/w 4 Core 1.00mm 4m LS0H DCA	K4P64AXR4M1DCA
P64AXR c/w 4 Core 1.00mm 5m LS0H DCA	K4P64AXR5M1DCA



S27

3 Pin Plug Socket Outlets

- 6A socket outlets are used in conjunction with 6A plugs to provide a pluggable connection to luminaires.
- Complies with BS 6972 and BS 5733
 - Suitable for use with standard Klik 3 pin plug
 - S27 socket is supplied in plug-in ceiling rose, Cat. Ref. PCR2000
 - S27 socket will accept A1 cover
 - S26/TC socket is an S26 architrave socket pre-assembled with a trunking clamp

Description	Cat ref.
3 Pin Round Socket White	S27



S64AX

4 Pin with Auxiliary Plug Socket Outlets

- klik.AX 6A socket outlets are used in conjunction with klik.AX 6A plugs to provide a pluggable connection to luminaires.
- Complies with BS 6972 and BS 5733
 - Suitable for use with standard klik.LDS 3 pin plug
 - S27 socket is supplied in plug-in ceiling rose, Cat. Ref. PCR2000
 - S27 socket will accept A1 cover
 - S26/TC socket is an S26 architrave socket pre-assembled with a trunking clamp
 - All sockets have 5 terminations: line, neutral, CPC, auxiliary and loop-in
 - Can be used with klik 3 or 4 pin plug

Description	Cat ref.
KLIK-AX 4-PIN ROUND SOCKET WHT	S64AX
4 PIN SOCKET BLACK 6A	S64BLACK



Moulded Mounting Boxes

- Complies with BS 5733

Description
Round Surface Box-30mm Deep

Cat ref.
MB2

MB2