



WMCS11

Light Switches

- Complies with BS EN 60669-1.
- 'X' rated - no need to derate for uorescent loads.
- Earth terminal in base.
- Switch will operate at up to an angle of 45 degrees.
- Pull cords 1.5m long.
- Capacity of each terminal: 2 x 1.5mm² conductors.

Description

6A Ceiling Switch 1 Way
6A Ceiling Switch 2 Way

Cat ref.

WMCS11
WMCS12



WMCS3PIF

Fan Isolator Switches

- Complies with BS EN 60669-2-4
- Rated conditional short circuit current (Inc) 1500A tested with Hager MTN110 6kA B Curve MCB.
- Terminal capacity: 3 x 1.5mm².
- Supplied with M3.5 x 30mm long xing screws.

Description

10A 3P Ceiling Switch Marked FAN & ISOLATOR

Cat ref.

WMCS3PIF
WMCS3PI
WMCS3PF



WMCS50N

Shower Switches

- Complies with BS EN 60669-2-4.
- Rated conditional short circuit current (Inc) 1500A tested with Hager MTN150 6kA B Curve MCB.
- Suitable for use with showers up to 11.5kW.
- Position of the contacts shown by flag indicator.
- Supplied with M3.5 x 30mm xing screws.
- Capacity of each terminal: 1 x 16mm² conductor.

Description

50A DP Ceiling Switch With LED Indicator

Cat ref.

WMCS50N