Product data sheet EG103B





EG103B

| Technical Properties | |
|---|-------------------|
| Number of modules | 2 |
| Type of contacts | 1 changeover |
| Rated operational voltage Ue | 195 / 230 / 265 V |
| Max. power with incandescent lamps | 2300 W |
| Fixing mode | Din-Rail |
| Frequency | 50/60 Hz |
| Number of channels | 1 |
| Summer / Winter time change | automatic |
| Shortest switching time | 1 mn |
| DCF | no |
| With holidays program | no |
| Width of installed product | 36 mm |
| Height of installed product | 85 mm |
| Length | 85 mm |
| Depth of installed product | 64 mm |
| Number of contacts | 1 |
| Number of program steps | 56 |
| Working accuracy | 9 |
| Protection index IP | IP20 |
| Total power loss under IN | 2 W |
| Power dissipation per coil | 0,5 W |
| Supply failure reserve | 5 years |
| Connection cross-sect. rigid cable | 1,5 / 10mm² |
| Connection cross-sect. flexible conductor | 1 / 6mm² |
| Operating temperature | -5 55 °C |
| Storage/transport temperature | -20 70 °C |
| Supply voltage | 230V AC |
| Breaking capacity | 16A 250V AC1 |
| Cycle | weekly |
| Programming cycle | 1X7D. |
| Type of programming | digital |
| Type of connection | with screw |
| | |

1 channel digi timeswitch weekly cycle